

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Issued by DBI Certification, notified body No. 2531.

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

Product group 1

for application as flooring,

produced by or for

Skamol A/S
Østergade 58-60
DK-7900 Nykøbing Mors

and produced in the manufacturing plant (s)

CXO10001

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 14306:2009 : **Thermal insulation products for building equipment and**
EN 14306:2009 + A1:2013 **industrial 2013Ainstallations – Factory made calcium**
silicate (CS) products - Specification

under system 1 are applied and that the product fulfils (products fulfil) the essential characteristic of **reaction to fire: Class A1.**

The attached 2 annexes forms part of this certificate.

This certificate was issued on **2014-08-01** and will remain valid as long as the test methods and/or factory production control requirements included in the harmonized standard, used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

(This certificate supersedes the previous version of this certificate, issued 2011-10-03 by NB 0845.)



Tom Nisted



Merete Poulsen

The certificate should only be reproduced extenso
– in extracts only with a written agreement with DBI Certification A/S.

DBI Certification A/S

Jernholmen 12, 2650 Hvidovre
Tlf.: 36 34 90 90

E-mail: info@dbicertification.dk
www.dbicertification.dk



DANAK
Prod. Reg. Nr. 7023

Version 2014-07-30
Page **1** of **3**

Certificate No.: 2531 – CPR–CXO10001

Date: 2014-08-01



EXTENT

Type	Description
Skamotec 225, SuperPro 225, Skamotec 250, SuperPro 250, Skamotec 300, SuperPro 300 and Skamotec-C	Calcium silicate boards with density of 225 - 300 kg/m ³ , maximum dimensions 2440 x 1220 mm, maximum thickness 100 mm

The certificate should only be reproduced extenso
– in extracts only with a written agreement with DBI Certification A/S.

DBI Certification A/S

Jernholmen 12, 2650 Hvidovre
Tlf.: 36 34 90 90

E-mail: info@dbicertification.dk
www.dbicertification.dk



Version 2014-07-30
Page 2 of 3

TEST DOCUMENTATION

Accredited Laboratory	Report no.	Date
DBI	PF13386	2010-09-22
DBI	PC10253	2010-09-22

TECHNICAL BASIS

Designation	Identification	Date
Product specification for Skamotec 225, SuperPro 225, Skamotec 250, SuperPro 250, Skamotec 300, SuperPro 300 and Skamotec-C		2011-10-03
Supplementary information	R12.001, Rev.nr. 38 R12.002, Rev.nr. 34 R12.004, Rev.nr. 34	2011-09-09 2010-02-25 2010-02-25

The certificate should only be reproduced extenso
– in extracts only with a written agreement with DBI Certification A/S.

DBI Certification A/S

Jernholmen 12, 2650 Hvidovre
Tlf.: 36 34 90 90

E-mail: info@dbicertification.dk
www.dbicertification.dk